



NVIDIA Rubin SXM vs NVIDIA Rubin CPX

Side by side datacenter GPU specifications from the Flopper.io database.

OVERVIEW

	NVIDIA Rubin SXM	NVIDIA Rubin CPX
FP32 TFLOPS	130.0	—
VRAM	288 GB	128 GB
Memory Bandwidth	22.0 TB/s	—
TDP	—	—

PERFORMANCE BY PRECISION

Precision	NVIDIA Rubin SXM peak TFLOPS (dense)	NVIDIA Rubin CPX peak TFLOPS (dense)
INT8	250.0	—
FP8	17500.0	—
FP16	4000.0	—
BF16	4000.0	—
TF32	2000.0	—
FP32	130.0	—
FP64_TC Tensor Core	200.0	—
FP64	33.0	—
FP32_TC Tensor Core	400.0	—
FP6	17500.0	—
NVFP4	35000.0	—

SPECIFICATIONS

	NVIDIA Rubin SXM	NVIDIA Rubin CPX
Architecture	Rubin	Rubin
Process Node	—	—
Launch Year	2026	2026

	NVIDIA Rubin SXM	NVIDIA Rubin CPX
Form Factor	SXM	—
Memory Type	HBM4	GDDR7
Interface Width	—	—
Interconnect	NVLink	—
TDP	—	—
FP32 Efficiency	—	—